

# VL-PS Power Supply Module

## Description

The VL-PS power supply module is designed to provide stable powering for all modules in the chassis. Two VL-PS modules can be used in one VLink platform redundancy with built-in power sharing circuitry. The auto-recovery short circuit protection function of the power supply improves the reliability of the platform. On the front panel, the LEDs indicate module status and DC voltage output status. VL-PS also provides 24 DC test point voltage testing for output.



## Specifications

Parameter	Unit	Specification	Note
<b>Power</b>			
Input AC voltage	VAC	85 to 264	--
Input connector		IEC male	--
Output DC voltage	W	24VDC/300W	--
Efficiency	--	Typical 86% Typical 84%	230VAC full loading 115VAC full loading
Short circuit protection	--	Yes	
<b>Other</b>			
Operation temperature	°C	0 to 50	--
Storage temperature	°C	-40 to 70	--
Humidity	%	Max 85% , non-condensing	--
Dimensions	mm	395Dx48Wx128H	--
Weight	Kg	2	--

## Features

- 90 to 264 VAC wide range
- 24 VDC/300W output
- Hot-swap capability
- Built in power sharing circuit
- Auto-recovery short circuit protection
- Integrated fans for localized cooling
- LEDs for module status indication

## Ordering Information

VL	--	PS	--	XX
				Customer specify